



RECOMMENDED PCB LAYOUT



CONTACTS	DIMENSIONS	
	A	B
4	3.00	4.00
5	4.00	5.00
6	5.00	6.00
7	6.00	7.00
8	7.00	8.00
9	8.00	9.00
10	9.00	10.00
11	10.00	11.00
12	11.00	12.00
13	12.00	13.00
14	13.00	14.00
15	14.00	15.00
16	15.00	16.00
17	16.00	17.00
18	17.00	18.00
19	18.00	19.00
20	19.00	20.00
21	20.00	21.00
22	21.00	22.00
23	22.00	23.00
24	23.00	24.00
25	24.00	25.00
26	25.00	26.00
27	26.00	27.00
28	27.00	28.00
29	28.00	29.00
30	29.00	30.00
31	30.00	31.00
32	31.00	32.00
33	32.00	33.00
34	33.00	34.00
35	34.00	35.00
36	35.00	36.00
37	36.00	37.00
38	37.00	38.00
39	38.00	39.00
40	39.00	40.00



No. of Contacts: 04 to 40
 Contact Plating:
 A = Gold Flash All Over
 C = Tin All Over
Standard = Gold Flash All Over

REQUEST SAMPLES AND QUOTATION

Packing Options
G = Plastic Box (Standard)
 D = Tube
 E = Tube with Cap

Insulator Material
L = LCP (Standard)

Dimension C (1/100mm) (Post Height)
Standard - 2.00mm = 0200
Standard - 2.40mm = 0240
Standard - 3.80mm = 0380
 or specify Dimension C
 e.g. 2.50mm = 0250
 Tol +/- 0.2mm

Dimension D (1/100mm) (Tail Length)
Standard - 1.60mm = 0160
Standard - 3.00mm = 0300
 or specify Dimension D
 e.g. 2.50mm = 0250
 Tol +/- 0.2mm

SPECIFICATIONS 规格:

CURRENT RATING 电流额定值: 1 AMP
 INSULATOR RESISTANCE 绝缘电阻值: 1000 MEGOHMS MIN.
 DIELECTRIC WITHSTANDING 耐电压: AC 300 V
 CONTACT RESISTANCE 接触电阻值: 20mΩ Max.
 OPERATING TEMPERATURE 工作温度: -40°C TO +105°C
 CONTACT MATERIAL 端子物料: COPPER ALLOY
 INSULATOR MATERIAL 绝缘体物料:
 STANDARD 标准物料: POLYESTER 聚酯, LCP, UL 94-V0
 SOLDERING PROCESS 可焊性:
 LCP (STANDARD 标准物料) -
 IR REFLOW 回流焊: 260°C for 10 sec. Δ
 WAVE 波峰焊: 250°C for 5-10 sec
 MANUAL SOLDER 人工焊接: 350°C for 3-5 sec Δ

MATES WITH 配套之母座 (SUBJECT TO PIN LENGTH 在端子长度适合的条件下):
 BC065 BC070 BC075

By	ASE	GG	SA	SA	SA
DETAIL	DRAWING RELEASE	CHANGE TO SOLDER TEMP. INFORMATION	AMENDMENT TO STANDARD DIMENSIONS	AMENDMENT TO PLATING OPTIONS	AMENDMENT TO ORDERING GRID
REV	A	B	C	D	E
DATE	20/05/08	23/07/09	08/12/09	21/12/09	05/01/10
1					
2					
3					



Tolerances (Except as noted)		Part Number:-	Date:-
Dimensions in mm		BC020	20 MAY 08
X. ± 0.30	X.° ± 5°	Description:-	
X.X ± 0.25	.X° ± 3°	1.0mm PITCH PIN HEADER, SINGLE ROW, THROUGH-HOLE, VERTICAL	
X.XX ± 0.15	.XX° ± 2°	THIS DRAWING IS CONFIDENTIAL AND MUST NOT BE COPIED OR DISCLOSED WITHOUT WRITTEN CONSENT	
X.XXX ± 0.10	.XXX° ± 1°	Scale NTS	
Third Angle Projection		Revision E	

GCT

www.globalconnectortechnology.com

Scale	Revision	Material	Drawn by	Sheet No.
NTS	E	See Note	ASE	E & OE 1/1