



CONTACTS	DIMENSIONS	
	A	B
4	3.00	4.00
5	4.00	5.00
6	5.00	6.00
7	6.00	7.00
8	7.00	8.00
9	8.00	9.00
10	9.00	10.00
11	10.00	11.00
12	11.00	12.00
13	12.00	13.00
14	13.00	14.00
15	14.00	15.00
16	15.00	16.00
17	16.00	17.00
18	17.00	18.00
19	18.00	19.00
20	19.00	20.00
21	20.00	21.00
22	21.00	22.00
23	22.00	23.00
24	23.00	24.00
25	24.00	25.00
26	25.00	26.00
27	26.00	27.00
28	27.00	28.00
29	28.00	29.00
30	29.00	30.00
31	30.00	31.00
32	31.00	32.00
33	32.00	33.00
34	33.00	34.00
35	34.00	35.00
36	35.00	36.00
37	36.00	37.00
38	37.00	38.00
39	38.00	39.00
40	39.00	40.00

Ordering Grid: BC025-XX-X-XXXX-XXXX-XXXX-L-X REQUEST SAMPLES AND QUOTATION

No. of Contacts: 04 to 40
 Contact Plating: A = Gold Flash All Over, C = Tin All Over
Standard = Gold Flash All Over

Packing Options:
G = Plastic Box (Standard)
 D = Tube
 E = Tube with Cap
 Insulator Material:
L = LCP (Standard)

Dimension C (1/100mm) (Post Height): **Standard - 2.00mm = 0200** or specify Dimension C e.g. 2.50mm = 0250 Tol +/- 0.2mm
 Dimension D (1/100mm) (Tail Length): **Standard - 2.00mm = 0200** or specify Dimension C e.g. 2.50mm = 0250 Tol +/- 0.2mm

SPECIFICATIONS 规格:

CURRENT RATING 电流额定值: 1 AMP
 INSULATOR RESISTANCE 绝缘电阻值: 1000 MEGOHMS MIN.
 DIELECTRIC WITHSTANDING 耐电压: AC 300 V
 CONTACT RESISTANCE 接触电阻值: 20mΩ Max.
 OPERATING TEMPERATURE 工作温度: -40°C TO +105°C
 CONTACT MATERIAL 端子物料: COPPER ALLOY
 INSULATOR MATERIAL 绝缘体物料:
 STANDARD 标准物料: POLYESTER 聚酯, LCP, UL 94-V0
 SOLDERING PROCESS 可焊性:
 LCP (STANDARD 标准物料) -
 IR REFLOW 回流焊: 260°C for 10 sec.
 WAVE 波峰焊: 250°C for 5-10 sec
 MANUAL SOLDER 人工焊接: 350°C for 3-5 sec

MATES WITH 配套之母座 (SUBJECT TO PIN LENGTH 在端子长度适合的条件下):
 BC065 BC070 BC075

By	ASE	GG	SA
DETAIL	DRAWING RELEASE	CHANGE TO SOLDER TEMP. INFORMATION	AMENDMENT TO PLATING OPTIONS
REV DATE	A 20/05/08	B 23/07/09	C 21/12/09



Tolerances (Except as noted)	Part Number:-	Date:-
Dimensions in mm	BC025	20 MAY 08
X: ± 0.30 X: ± 5° X.X ± 0.25 X: ± 3° X.XX ± 0.15 XX: ± 2° X.XXX ± 0.10 XXX: ± 1°	Description:-	
Third Angle Projection	1.0mm PITCH ELEVATED PIN HEADER, SINGLE ROW, THROUGH HOLE, VERTICAL	
	THIS DRAWING IS CONFIDENTIAL AND MUST NOT BE COPIED OR DISCLOSED WITHOUT WRITTEN CONSENT	



www.globalconnectortechology.com

Scale NTS	Revision C	Material See Note	Drawn by ASE	Sheet No. E & OE 1/1
-----------	------------	-------------------	--------------	----------------------