



RECOMMENDED PCB LAYOUT
(Tolerance: ±0.05)

CONTACTS	DIMENSIONS	
	A	B
2	1.00	2.00
3	2.00	3.00
4	3.00	4.00
5	4.00	5.00
6	5.00	6.00
7	6.00	7.00
8	7.00	8.00
9	8.00	9.00
10	9.00	10.00
11	10.00	11.00
12	11.00	12.00
13	12.00	13.00
14	13.00	14.00
15	14.00	15.00
16	15.00	16.00
17	16.00	17.00
18	17.00	18.00
19	18.00	19.00
20	19.00	20.00
21	20.00	21.00
22	21.00	22.00
23	22.00	23.00
24	23.00	24.00
25	24.00	25.00
26	25.00	26.00
27	26.00	27.00
28	27.00	28.00
29	28.00	29.00
30	29.00	30.00
31	30.00	31.00
32	31.00	32.00
33	32.00	33.00
34	33.00	34.00
35	34.00	35.00
36	35.00	36.00
37	36.00	37.00
38	37.00	38.00
39	38.00	39.00
40	39.00	40.00

Ordering Grid

BC034-XX-X-X-XXXX-L-X

REQUEST SAMPLES AND QUOTATION

No. of Contacts
02 to 40

Contact Plating
A = Gold Flash All Over
C = Tin All Over
Standard = Gold Flash All Over

Insulator Height 'H'
V = 1.50mm
K = 1.27mm
(Standard 1.50mm)

Packing Options
C = Tape and Reel with Film (Standard)
D = Tube
E = Tube with Cap
Insulator Material
L = LCP (Standard)
Dimension C (1/100mm)
(Post Height)
Standard - 1.50mm = 0150
or specify Dimension C
e.g. 2.50mm = 0250
Tol +/- 0.2mm

SPECIFICATIONS 规格:

CURRENT RATING 电流额定值: 1 AMP
INSULATOR RESISTANCE 绝缘电阻值: 1000 MEGOHMS MIN.
DIELECTRIC WITHSTANDING 耐电压: AC 300 V
CONTACT RESISTANCE 接触电阻值: 20mΩ Max.
OPERATING TEMPERATURE 工作温度: -40°C TO +105°C
CONTACT MATERIAL 端子物料: PHOSPHOR BRONZE
INSULATOR MATERIAL 绝缘体物料:
STANDARD 标准物料: POLYESTER 聚酯, LCP, UL 94-V0
SOLDERING PROCESS 可焊性:
LCP (STANDARD 标准物料) -
IR REFLOW 回流焊: 260°C for 10 sec.
WAVE 波峰焊: 250°C for 5-10 sec
MANUAL SOLDER 人工焊接: 350°C for 3-5 sec

MATES WITH 配套之母座 (SUBJECT TO PIN LENGTH 在端子长度适合的条件下):
BC065 BC070 BC075

By	ASE	SA	SA	SA
DETAIL	DRAWING RELEASE	AMENDMENT TO PLATING OPTIONS AND SPEC	INSULATOR OPTIONS MODIFIED	PACKING STANDARD MODIFIED
REV DATE	A 20/05/08	B 21/12/09	C 09/04/10	D 21/07/10



Tolerances (Except as noted)	Part Number:-	Date:-
Dimensions in mm X. ± 0.30 X.° ± 5° X.X ± 0.25 X.° ± 3° X.XX ± 0.15 XX° ± 2° X.XXX ± 0.10 XXX° ± 1°	BC034	20 MAY 08
Third Angle Projection	Description:- 1.00mm PITCH PIN HEADER, SINGLE ROW, SURFACE MOUNT, HORIZONTAL	
	THIS DRAWING IS CONFIDENTIAL AND MUST NOT BE COPIED OR DISCLOSED WITHOUT WRITTEN CONSENT	

GCT

www.globalconnectortech.com

Scale	Revision	Material	Drawn by	Sheet No.
NTS	D	See Note	ASE	E & OE 1/1